











8

3

230 384

1



*

JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(43) Date of publication of application: 10.09.1993 (11) Publication number:

05236437 A

H04N 5/445 H04N 7/08 (51) Int. CI

04031047 (21) Application number:

18.02.1992 (22) Date of filing:

(54) TELETEXT RECEIVER

(57) Abstract:

tion designated by a display position input means cor-PURPOSE: To improve operability in the case of selecting the program of character broadcasting by executing correspondent program display when the display contents of characters displayed at a display posirespond to a program number.

period)-16H and 21H in the vertical flyback periods ter broadcasting superimposed on 14H (H:horizontal of outputted intermediate video frequency signals are sampled by a sampling circuit 3 and stored in a RAM ceived are tuned by a tuner 2, and signals for charac-5 as display code data after correcting error at an error correction circuit 4. A controller 9 stores data for dis-CONSTITUTION: TV radio waves desired to be replay in a memory 6 for display by referring to the dis-


(71) Applicant: PIONEER ELECTRON CORP

KURODA KAZUO (72) Inventor:

HASEBE TAKESHI

vice 10 and decides an executing processing from the obtained coordinate of the mouse. When the display 8 and displays pictures on a display 7. The controller 9 detects the coordinates of a mouse as a pointing decontents correspond to the program number of a cerplay code data in the RAM 5 and a character memory tain program, the controller 9 displays the correspondent program.

COPYRIGHT: (C)1993, JPO& Japio



file:///CJ/Documents%20and%20Settings/deeptid/Desktop/dl/JP05236437A2.htm (1 of 2) [8/18/2005 2:34:13 PM]



file:///CI/Documents%20and%20Settings/deeptid/Desktop/dI/JP05236437A2.htm (2 of 2) [8/18/2005 2:34:13 PM]